
# **Digital Control Station**

Model No. CDS-4CM





- COMMAX Co.,Ltd. Thank you for purchasing our COMMAX product.
   Please carefully read this User's Guide (in particular, precautions for safety) before using the product and follow the instructions to use your product exactly.
  - The company is not responsible for any safety accidents caused in abnormal operation of the product.



1. Features and Function
2. System Layout
3. Wiring Diagram
4. Specification
5. Wiring method and How to use

COMMAX Co.,Ltd.

## Warnings and caution


Make sure to follow the instructions to prevent any danger or property losses.



Warning Death or serious injury is expected.

It indicates prohibition.

It indicates prohibition of disassembly.





It indicates dos and don'ts.



It indicates that the plug should be pulled out from the socket.







It may generate abnormal heat




Do not forcibly bend the cord or put a heavy object on the product. It may cause breakdown.

It may cause a fire







Make sure to wash it by using a dry cloth to prevent any breakdown or electric shock.



Do not put the plug in the socket with a wet hand. It may cause an electric shock.



Do not install the product in a humid place. It may cause an electric shock or



Do not disassemble, repair or modify the product. It may cause a fire, an electric shock or an injury due to malfunction of the



Do not forcibly pull out the

If the cord is damaged, it may

cause a fire or an electric shock.


cord from the socket.

Do not use AC circuit breaker. It may cause an electric shock.

## Warnings and caution



Caution An injury or property losses are expected



It indicates prohibition of disassembly.



It indicates prohibition of contact. It indicates dos and don'ts.



It indicates that the plug should be pulled out from the socket.











than normal, do not put the

It may cause an electric shock

substances are not gathered on the product.

Make sure that dust or foreign

product.

Make sure to prevent foreign substances from entering the

It may cause a breakdown.






Do not put a heavy object on

It may cause a breakdown

the product.









Avoid direct rays of the sun or heating devices at a time of installation.



Install the product in a flat and stable place. Otherwise, it may not function



not used for a long time.






Pull the plug if the product is If the product generates strange sound, make sure to pull the plug immediately and contact Commax service center.

**COMMAX Co.,Ltd.** 

COMMAX Co.,Ltd.




### 1. Features

- Flush mouth type Digital Control Station
- Free Voltage power supply
- To be interfaces up-to 4<sup>th</sup> cameras
- To be interfaces up-to 20<sup>th</sup> monitors

### 2. Function


- Working with CAV-70B
- Working with DPV-nAS
- Working with Alarm Sensor

## 2. System Layout



- Maximum connect with up-to 4<sup>th</sup> cameras \*Available to connect with CCTV camera
- Maximum connect with up-to 20<sup>th</sup> monitors


# 3. Wiring Diagram




- Notes for connecting
- \_Maximum number per line from the slave connection terminal of main unit is 5.
- -Please connect wiring terminal carefully on polarity.
- \_Please use UTP (CAT. 5) for cable and 14~24AWG for others.

# 4. Specification

Model Model	CONTENTS(CDS-70M)
Transmisson	2 wires, 4wires at Entrance, 6wires at MASTER Unit
Rated voltage	DC15V
Power consumption	On standby: 100mA, On operating: 250mA
Telephone Conversation Distance	Entrance: 28M(CAT#5 cable)  MASTER Unit: 20M(0.65 cable, Video-out 3C2V Coaxial cable)







### 1. Wiring Method

- As the maximum, five Master-V/Ps can be connected with 1 line which is a master connection terminal of main unit.
  - ▶ The maximum 20 sets of Master-V/P can be connected with 1 main unit.
- In case of wiring between two Master-V/Ps, an video cable must be connected as a VD/IN and VD/OUT pair.
- Be careful of connection, as it is polarized cables.
  - ▶ In case of wrong connection, a video phone in a household shall not operate.
- Master ID (household video phone) must be input, unless master ID input, it shall not operate properly.

### 2. How to use

- In case of normal connection, it shall be connected with power cord, and then, turn on the power switch.
- LED shall operate, if power is on.
- Refer CAV-70B and DPV-NAS user guide for another operation method.
- DIP S/W shall be in accordance with the number of a camera connection. If three cameras connected, DIP S/W shall turn on 1, 2 and 3 switches.

**COMMAX Co.,Ltd.** 

COMMAX Co.,Ltd.



a513-11, Sangdaewon-dong, Jungwon-gu, Seongnam-si, Gyeonggi-do, Korea Int'l Business Dept.:
Tel.; +82-31-7393-540~550
Fax.; +82-31-745-2133
Web site: www.commax.com

Printed In Korea

