



Model	PTBKAD200
<b>Camera</b>	
Image Sensor	1/3" Panasonic 2MP CMOS Sensor
Horizontal Resolution	1080P
S/N Ratio	>50db
<b>PTZ</b>	
Horizontal Rotation Speed	30°/S
Horizontal Rotation Range	0°~160°
Tilt Rotation Speed	Manual
Tilt Rotation Range	-45°~25°
Auto Flip	No Support
Ratio Speed	Support
360° Scan	No Support
A-B Scan	Support
Preset Points	220
Guard Tours	3 groups
Guard Points	Max.16 points
<b>Lens</b>	
Focus Length	5mm-50mm
Focus Control	10X Optical Zoom
<b>Night Vision</b>	
Infrared LED	35μx4PCS
IR Range	30m
Auto Control IR LED	PWM
<b>Communication</b>	
Communication Protocol	Pelco-D, Pelco-P
Communication interface	RS485
Baud Rate	1200/2400/4800/9600bps
<b>General</b>	
Weatherproof	IP66
Operating Temperature	Indoor: 0°~ +40° Outdoor: -20°~ +60°
Operating Humidity	≤90% Non Condensing
Heater & Blower	Auto temperature control
Power	DC12V/2A
Lightning Protection	Transient voltage 6000V
Dimension	26.5x13.7x13(mm)
Weight	1.3Kgs