



◆ SPECIFICATION

Model NO.	LBR30S100	LBR30S130	LBR30S130	LBR30S200	LBR30S200	LBR30S200	LBR30S200	LBR30S200	LBR30A200	LBR30AL200	LBR30S300	LBR30A300	LBR30S400	LBR30A400
Camera														
Image Sensor	OV9732	S3130	IMX225	IMX323	IMX323	OV2718	IMX290	IMX322	IMX290	IMX123	IMX123	OV4689	OV4689	
Main processor	HI3518EV200	HI3518EV200	HI3518EV200	HI3516CV200	HI3518EV200	HI3516CV200	HI3516D	S2L33	S3L33	HI3516D	S2L55	HI3516D	S2L55	
Resolution	720P	960P	960P	1080P	1080P	1080P	1080P	1080P	1080P	3MP	3MP	4MP	4MP	
Effective Pixels	1280(H)*720(V)	1280(H)*960(V)	1305(H)*977(V)	1985(H)*1105(V)	1920(H)*1080(V)	1920(H)*1080(V)	1945(H)*1097(V)	1984(H)*1225(V)	1945(H)*1097(V)	2065(H)*1553(V)	2065(H)*1553(V)	2688(H)*1520(V)	2688(H)*1520(V)	
Compression	H.264/JPEG/AVI/MJPEG	H.264/JPEG/AVI/MJPEG	H.264/JPEG/AVI/MJPEG	H.264/JPEG/AVI/MJPEG	H.264/JPEG/AVI/MJPEG	H.264/JPEG/AVI/MJPEG	H.264/H.265/JPEG/AVI/MJPEG	H.264/JPEG/AVI/MJPEG	H.264/H.265/JPEG/AVI/MJPEG	H.264/H.265/JPEG/AVI/MJPEG	H.264/JPEG/AVI/MJPEG	H.264/H.265/JPEG/AVI/MJPEG	H.264/JPEG/AVI/MJPEG	
TV System	PAL/NTSC													
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec													
S/N Ratio	≥52dB													
Scanning System	Progressive													
Video Output	Network													
Focus Length	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm
Focus Control	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed
Lens Type	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed
Pixels	2MP	2MP	2MP	3MP	3MP	3MP	3MP	3MP	3MP	3MP	4MP	4MP	4MP	4MP
Night Vision														
Infrared LED	42μ x 2PCS													
Infrared Distance	30M													
IR Status	Under 10 Lux By CDS													
IR Power On	CDS Auto Control													
Network														
Ethernet	RJ-45 (10/100Base-T)													
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTSP,RTCP,NTP,SMTP													
ONVIF	Support ONVIF 2.4													
P2P	YES, Support QR Code													
POE	Optional, Support IEEE 802.3af													
WIFI	N/A													
Video Delay	0.3S (Within the Lan)													
Main Stream 1	1280*720@25fps	1280*960@25fps	1280*960@25fps	1920*1080@25fps	1920*1080@15fps	1920*1080@25fps	1920*1080@30fps	1920*1080@30fps	1920*1080@30fps	2048*1536@30fps	2048*1536@30fps	2560*1440@20fps	2560*1520@20fps	
Main Stream 2	/	1280*720@25fps	/	/	/	/	/	/	/	1920*1080@30fps	1920*1080@30fps	2304*1296@30fps	2048*1520@20fps	
Main Stream 3	/	/	/	/	/	/	/	/	/	/	/	1920*1080@30fps	1920*1080@20fps	
Sub Stream 1	720*480@25fps	720*480@25fps	720*480@25fps	720*480@25fps	720*480@15fps	720*480@25fps	720*480@30fps	720*576@30fps	720*576@30fps	720*480@30fps	720*480@30fps	720*480@20fps	720*480@20fps	
Sub Stream 2	/	/	/	/	/	/	/	720*480@30fps	720*480@30fps	/	640*360@30fps	/	640*360@20fps	
Sub Stream 3	/	/	/	/	/	/	/	640*360@30fps	640*360@30fps	/	/	/	/	
Tri Stream	352*288@25fps	/	/	352*288@25fps	352*288@15fps	352*288@25fps	352*288@30fps	352*288@30fps	352*288@30fps	352*288@30fps	352*288@30fps	352*288@20fps	352*288@20fps	
IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari													
Smart Phone	iPhone, iPad, Android, Android Pad													
Camera Features														
Day/Night	Color/ B&W (IR-CUT)													
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)													
Corridor Pattern	/	/	/	/	/	/	Support	/	/	Support	/	Support	/	
Defog Mode	Support	Support	Support	Support	Support	Support	Support	/	/	Support	/	Support	/	
ROI	Support	Support	Support	Support	Support	Support	Support	/	/	Support	/	Support	/	
BLC	Support	Support	Support	Support	Support	Support	Support	/	/	Support	/	Support	/	
HDR	/	/	/	/	/	/	/	/	Support	Support	/	/	Support	
WDR	Support													
Motion Detection	Support													
Privacy Masking	3 Rectangular Zone													
Recording Mode	NVR/NAS/CMS/Web													
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands													
General														
Housing	Metal, IP66													
Anti-cut Bracket	YES													
IR Cut Filter	YES													
Operation Temperature	-20℃ ~ +60℃ RH95% Max													
Storage Temperature	-20℃ ~ +60℃ RH95% Max													
Power Source	DC12V±10%, 700mA													
Dimension	194(W) x 66(H) x 67(D)mm													
Weight	850g													