



◆ SPECIFICATION

Model NO.	LBR30S100	LBR30S130	LBR30S130	LBR30S200	LBR30S200	LBR30S200	LBR30S200	LBR30S200	LBR30S200	LBR30S200	LBR30S200	LBR30S200	LBR30S200
<b>Camera</b>													
Image Sensor	OV9732	S3130	IMX225	IMX323	IMX323	OV2718	IMX290	IMX322	IMX290	IMX123	IMX123	OV4689	OV4689
Main processor	HI3518EV200	HI3518EV200	HI3518EV200	HI3516CV200	HI3518EV200	HI3516CV200	HI3516D	S2L33	S3L33	HI3516D	S2L55	HI3516D	S2L55
Resolution	720P	960P	960P	1080P	1080P	1080P	1080P	1080P	1080P	3MP	3MP	4MP	4MP
Effective Pixels	1280(H)*720(V)	1280(H)*960(V)	1305(H)*977(V)	1985(H)*1105(V)	1920(H)*1080(V)	1920(H)*1080(V)	1945(H)*1097(V)	1984(H)*1225(V)	1945(H)*1097(V)	2065(H)*1553(V)	2065(H)*1553(V)	2688(H)*1520(V)	2688(H)*1520(V)
Compression	H.264/JPEG/AVI/MJPEG	H.264/JPEG/AVI/MJPEG	H.264/JPEG/AVI/MJPEG	H.264/JPEG/AVI/MJPEG	H.264/JPEG/AVI/MJPEG	H.264/JPEG/AVI/MJPEG	H.264/H.265/JPEG/AVI/MJPEG	H.264/JPEG/AVI/MJPEG	H.264/H.265/JPEG/AVI/MJPEG	H.264/H.265/JPEG/AVI/MJPEG	H.264/JPEG/AVI/MJPEG	H.264/H.265/JPEG/AVI/MJPEG	H.264/JPEG/AVI/MJPEG
TV System	PAL/NTSC												
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec												
S/N Ratio	≥52dB												
Scanning System	Progressive												
Video Output	Network												
Focus Length	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm
Focus Control	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed
Lens Type	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed
Pixels	2MP	2MP	2MP	3MP	3MP	3MP	3MP	3MP	3MP	4MP	4MP	4MP	4MP
<b>Night Vision</b>													
Infrared LED	42μ x 2PCS												
Infrared Distance	30M												
IR Status	Under 10 Lux By CDS												
IR Power On	CDS Auto Control												
<b>Network</b>													
Ethernet	RJ-45 (10/100Base-T)												
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTSP,RTCP,NTP,SMTP												
ONVIF	Support ONVIF 2.4												
P2P	YES, Support QR Code												
POE	Optional, Support IEEE 802.3af												
WIFI	N/A												
Video Delay	0.3S (Within the Lan)												
Main Stream 1	1280*720@25fps	1280*960@25fps	1280*960@25fps	1920*1080@25fps	1920*1080@15fps	1920*1080@25fps	1920*1080@30fps	1920*1080@30fps	1920*1080@30fps	2048*1536@30fps	2048*1536@30fps	2560*1440@20fps	2560*1520@20fps
Main Stream 2	/	1280*720@25fps	/	/	/	/	/	/	/	1920*1080@30fps	1920*1080@30fps	2304*1296@30fps	2048*1520@20fps
Main Stream 3	/	/	/	/	/	/	/	/	/	/	/	1920*1080@30fps	1920*1080@20fps
Sub Stream 1	720*480@25fps	720*480@25fps	720*480@25fps	720*480@25fps	720*480@15fps	720*480@25fps	720*480@30fps	720*576@30fps	720*576@30fps	720*480@30fps	720*480@30fps	720*480@20fps	720*480@20fps
Sub Stream 2	/	/	/	/	/	/	/	720*480@30fps	720*480@30fps	/	640*360@30fps	/	640*360@20fps
Sub Stream 3	/	/	/	/	/	/	/	640*360@30fps	640*360@30fps	/	/	/	/
Tri Stream	352*288@25fps	/	/	352*288@25fps	352*288@15fps	352*288@25fps	352*288@30fps	352*288@30fps	352*288@30fps	352*288@30fps	352*288@30fps	352*288@20fps	352*288@20fps
IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari												
Smart Phone	iPhone, iPad, Android, Android Pad												
<b>Camera Features</b>													
Day/Night	Color/ B&W (IR-CUT )												
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)												
Corridor Pattern	/	/	/	/	/	/	Support	/	/	Support	/	Support	/
Defog Mode	Support	Support	Support	Support	Support	Support	Support	/	/	Support	/	Support	/
ROI	Support	Support	Support	Support	Support	Support	Support	/	/	Support	/	Support	/
BLC	Support	Support	Support	Support	Support	Support	Support	/	/	Support	/	Support	/
HDR	/	/	/	/	/	/	/	/	Support	Support	/	/	Support
WDR	Support												
Motion Detection	Support												
Privacy Masking	3 Rectangular Zone												
Recording Mode	NVR/NAS/CMS/Web												
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands												
<b>General</b>													
Housing	Metal, IP66												
Anti-cut Bracket	YES												
IR Cut Filter	YES												
Operation Temperature	-20℃ ~ +60℃ RH95% Max												
Storage Temperature	-20℃ ~ +60℃ RH95% Max												
Power Source	DC12V±10%, 700mA												
Dimension	194(W) x 66(H) x 67(D)mm												
Weight	850g												